

ALLINONE TRACTOR OIL

PRODUCT DESCRIPTION

ALLINONE Tractor Oil is specially designed to meet all the necessary lubrication requirements found in any part of a modern tractor, such as engine, transmission, hydraulic system and wet brake.

Incorporated with the latest S.T.O.U. technology, ALLINONE Tractor Oil is available in different SAE multi-grades, and therefore can be used under all weather and season conditions. Furthermore, the “Only one oil for all parts lubricant” also can significantly reduce the inventory cost and eliminate the chances of using the “wrong oil”.

APPLICATIONS / BENEFITS

- High Engine performance.
- Only one oil for all parts lubrication.
- Extended service life.

TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS		
		10W30	15W40	20W40
SAE Viscosity Grade	SAE J300	10W30	15W40	20W40
Specific Gravity @ 15°C	ASTM D-4052	0.8860	0.890	0.8910
Flash Point, °C	ASTM D-92	200min	210min	220min
Pour Point, °C	ASTM D-97	- 18	- 15	- 15
Kinematics Viscosity @ 40°C (cSt)	ASTM D-445	71.3	103.7	128
@ 100°C (cSt)	ASTM D-445	11.2	14.32	14.42
Viscosity Index	ASTM D-2270	149	141	114
TBN (mgKOH/g)	ASTM D-2896	10.9	10.9	10.9
Colour	ASTM D-1500	< 4.5	< 4.5	< 4.5

PERFORMANCE STANDARDS

- API CF
- API GL-4,
- Mercedes Benz 227.1,
- John Deere J27,
- Massey Ferguson M1139/M1144,
- Allison C-4

- Ford ESN-M2C-159B.
- CCMC D4