

## ATF SP 2 PLUS

**PRODUCT DESCRIPTION**

Automatic Transmission Fluid SP 2 Plus is formulated with the latest generation fluid developed from patented hydrocracked basestock to meet the factory-filled requirement of Mitsubishi, Hyundai and Proton vehicles. This synthetic blend ATF is ashless and suitable for most Japanese made vehicles. SP 2 Plus is also suitable for other European made vehicles.

**APPLICATIONS / BENEFITS**

- ❑ Provides excellent friction, oxidation and thermal stability.
- ❑ Outstanding antiwear properties.
- ❑ Improves hydrolytic stability.
- ❑ Better flowability at cold temperature.

**TYPICAL CHARACTERISTICS**

<b>TEST DESCRIPTION</b>	<b>METHOD</b>	<b>TYPICAL RESULTS</b>
Specific Gravity @ 15 <sup>o</sup> C	ASTM D-4052	0.863
Flash Point, <sup>o</sup> C	ASTM D-92	204
Pour Point, <sup>o</sup> C	ASTM D-97	- 39
Kinematics Viscosity @40 <sup>o</sup> C (cSt)	ASTM D-445	36.7
@100 <sup>o</sup> C (cSt)		7.4
Viscosity Index	ASTM D-2270	173
Color		RED

**PERFORMANCE STANDARDS**

- Mitsubishi, Hyundai Factory Fill Requirements (SP II+)
- JASO 1A